




3-KNUCKLE FULL MORTISE CONCEALED BEARING

STANDARD WEIGHT 3 112" X 3 112" APX AP





GENERAL PRODUCT INFORMATION: PBB, Inc. template hinges are manufactured to close tolerances and meet all specifications and requirements set by the American National Standards Institute (ANSI).

HINGE SWAGING: A standard swaging of our standard weight full mortise hinge when closed to parallel position provides a 1/16" clearance between leaves.

MATERIAL GAUGE:

 $.123 \pm .005$ for 3-1/2" x 3-1/2" $.130 \pm .005$ for 4" x 4"

3-1/2" STANDARD SCREW SIZE FHMS - 10-24 x 1/2" FHWS - 10 x 1"

4" STANDARD SCREW SIZE

FHMS - 12-24 x 1/2" FHWS - 12 x 1-1/4"

CB81 (ANSI A8112)

Steel-Polished and Plated or Bonderized and Prime Coated for Painting.

CB21 (ANSI A2112)

Brass-Polished and Plated

CB51 (ANSI A5112) Stainless Steel-Polished and Satin Finish

- •For medium weight doors receiving medium frequency service.
- •Concealed bearing for trouble free long life application.
- •Non-rising removable pin.
- •Hole in bottom tip for easy pin removal.
- •Attractive slim barrel with flush pins and plugs.
- •May be used on fire rated openings.
- •For hospital type, add HT to suffix of part number
- •3-1/2", 4" available in square, 5/8" and 1/4" Radius Round Corners.
- •All hinges are ANSI template.

OTHER SPECIFICATIONS:

standard CS9-65.

Height of hinge: + .000 3.50 - .015 for 3-1/2"

4.00 + .000 Width: for 4"

 $3.50 \pm .015$ for 3-1/2" $4.00 \pm .015$ for 4"

Template screw hole locations for all 3-1/2" x 3-1/2" full mortise template butts are punched to commercial

PACKAGING INFORMATION:

One hinge per plastic bag, 3 hinges and 1 screw pack per unit carton.

16 unit carton or 48 hinges per master shipping carton.

1 screw pack includes all machine screws (24), and 1/2 wood screws (12). ATMS & AWS also available.

For 3-1/2" x 3-1/2", 1 screw pack includes (18) machine screws and (18) wood screws.