







CH53 SS PIN & BARREL SERIES

FULL SURFACE FLUSH MOUNT



Open Position



- ◆ No special door and frame preparation
- ◆ For beveled or square edged doors
- ◆ For 1 3/4" doors
- ◆ Supports door weights up to 600 lbs.
- ◆ 4'0" Maximum door width
- ◆ For high traffic, high abuse doors
- ◆ No exposed fasteners when door is closed
- ◆ Fully reversible - No handing required
- ◆ Install, clip and go system
- ◆ Material -Heavy-duty 13 gauge 304 Stainless Steel
- ◆ Self drilling screws
- ◆ 1/4" diameter stainless steel pin
- ◆ Decorative fastener covers
- ◆ Conforms to ANSI/BHMA 156.26, Grade 1
- ◆ UL/ULC fire listed on wood doors for up to 20 minutes
- ◆ UL/ULC fire listed on hollow metal & composite wood fire doors for 90 minutes
- ◆ UL/ULC fire listed on hollow metal doors for up to 3 hours
- ◆ Patent Pending
- ◆ Meets UL10B, UL10C, UBC 7-2.

PBB Model Number	Length		Screw Count	
	Inches	Centimeters	Door	Jamb
CH5379	79-1/8"	201.0	11	11
CH5383	83-1/8"	211.1	12	12
CH5385	85"	215.9	14	14
CH5395	95"	241.3	13	13
CH53119	118-3/4"	301.6	16	16

630 - Satin Stainless Steel - US32D

Full Surface Fasteners –

- a. Screw Pack 4 – 1/4-20 x 3/4" P.P.H. self drilling tek screws
PLEASE SPECIFY SCREW PACK REQUIREMENTS



CH53 SS PIN & BARREL SERIES

STANDARD HINGE LENGTH CONVERSION CHART

FULL SURFACE FLUSH MOUNT

A 85.00" ACTUAL LENGTH = A 7'2" DOOR OPENING	A 95.00" ACTUAL LENGTH = A 8' DOOR OPENING	A 118.75" ACTUAL LENGTH = A 10' DOOR OPENING
<p>*79.125" Field Cut Score Line</p> <p>*83.125" Field Cut Score Line</p>		

*Please refer to page 47, "Stainless Steel Continuous Hinge Field Cutting Instructions" for more information.